



Truck and Jeep Accessories

KJ71056BK

**2007-2016 Jeep Wrangler JK
A-Pillar Switch Pod w/ Switches**



www.Daystarweb.com

Tech Support Contact Info

Tech@DaystarWeb.com

Phone: 623.907.0081

Fax: 623.907.0088

841 South 71st Avenue

Phoenix, AZ 85043

Instruction Sheet: P21652

**2015 Daystar Products International
Inc.**

Revision: 1

Revision Date: 8/27/14

Revised by: PH

Introduction



is your number one source for Made In The USA quality vehicle accessories. Now backed with our exclusive Go *Everywhere* © Lifetime Limited

Warranty (see terms at Daystarweb.com). To ensure your safety and proper installation of this product, take a moment to read all instructions and product safety information before trying to install your Daystar® product. If you have technical questions after reading these instructions, we are here to help: contact us at 800-595-7659.

Product Safety Information

Throughout these instructions, important safety information is generally preceded by one of three signal words indicating the relative risk of injury. The signal words are as follows:

! WARNING A hazardous situation which, if not avoided, could result in death or serious injury. You can be seriously injured or killed if you don't follow instructions.

! CAUTION A hazardous situation which, if not avoided, could result in minor or moderate injury. You can be moderately injured and also may suffer property damage if you don't follow instructions.

NOTICE Careful attention is required to this instruction or operation, but this does not generally relate to personal injury. Damage to your product or other property may result if you don't follow instructions.

!WARNING

Familiarize yourself with all vehicle manufacturer and Daystar warnings, instructions, and limited warranties before driving your modified suspension vehicle. Also, be aware many states / countries have laws governing on-road vehicle heights and modifications. You are responsible for ensuring the safety and legality of your vehicle. A summary of current state vehicle laws is available at www.sema.org.

Tools Needed

Quantity	Description
1	Phillips screw driver
1	Needle nose pliers
1	T-20 Torx bit
1	1/4" Drive
1	Scissors
1	Dremel tool or body saw
1	Painters tape
1	X-Acto knife
1	Marker
1	Center Punch
1	1/16" drill bit
1	1/4" drill bit
1	Drill
1	File

Bill of Materials

Quantity	Part Number	Description
1	M56156-BK	A-Pillar Switch Pod
4	P21610	Push Retainer
1	P21612	Trim Template
1	P21611	Instructions
1	KU80011	Rocker Switch Blue
1	KU80012	Rocker Switch Green
1	KU80013	Rocker Switch Amber
1	KU80014	Rocker Switch Red

Installation Instructions

!Warning: Always work with appropriate personal safety gear including safety glasses, gloves and hearing protection if using air powered tools.

Begin by inspecting the components & hardware for damage, then compare components & hardware to the bill of materials for completeness. If anything is missing/damaged, do not proceed with the installation. Please call Daystar Products (800-595-7659) and we will send you the missing or damaged components free of charge.

1. Remove the Driver's side visor. To do this you will need to unscrew the 2 Torx bolts at the visor pivot. Use the T-20 Torx to accomplish this task.
2. Once the visor is removed, pull down on the corner trim panel. It is held in place with a fur tree connector, that mounts it to the windshield bar (Figure: 1)



3. Moving on to the A-pillar, with the Phillips screw driver remove the center of the push pin that retains the factory A-pillar. **TIP:** The treads on the center pin, are not very strong. Use light pressure when unscrewing the center pin. Once it is out far enough to grab with the needle nose pliers, switch tools, and remove the whole assembly (Figure: 2).



Figure: 2

4. Remove the A-pillar by, gently pulling back and up. It is held in place with 1 or 2 (depending on year) steel tension clips (Figure: 3).

5. Locate the pillar template.
Part number P21612.

6. Gather the following tools:
scissors,
tape,
marker,
drill, 1/16" and 1/4" drill bits,
Dremel, X-acto knife, and center punch.



Figure: 3

7. Cut out the trim template (Figure: 4).
8. Place the template onto the A-pillar. Start by matching up the right edge, paying attention to the roll bar notch at the top of the template. (Figure: 5)
9. Place tape along the right edge to hold the template in place.
10. Now that the template is secure wrap it around until the left edge of the template lines up with the left edge of the A-pillar.
11. Starting with the hole in the upper right hand corner, marked with a #1, center punch the hole (Figure: 6). **Do not center punch any of the other holes at this time.**




Figure: 4

12. With the 1/16" bit drill hole #1. **Use caution when drilling holes on the curve. The drill bit may try to walk, if it does a poor installation may result.**

13. Open the 1/16" hole to 1/4"



14. With the first hole drilled, grab the Daystar A-pillar switch pod and one of the push pins.

15. Remove the center pin from the push pin.


16. Place the Daystar switch pod onto the A-pillar and use the push pin to affix the switch pod to the pillar (Figure: 7)



Figure: 5




17. Align the Daystar switch pod lower right hand hole with hole #2, and center punch (Figure: 8). By drilling the holes one at a time we are ensuring that all 4 holes will line up. While this is a time consuming process it will allow for a trouble free install.




18. Drill hole #2 to 1/16" then open it up to 1/4"
19. Grab another push pin, remove the center pin and use it to hold the Daystar Switch Pod in place.
20. Center punch hole 3, drill the pilot hole, open it up to 1/4", install a push pin to hold in place.
21. Center punch hole 4, drill the pilot hole, open it up to 1/4".
22. Now that all of the Daystar switch pod mounting holes are located, remove the switch pod and set aside.
23. Center punch the 4 x 1/4" holes located in the center of the template (Figure: 9).



24. Drill the center punched holes out to $1/16''$
25. Open up each of the $1/16''$ pilot holes to $1/4''$ (Figure: 10).



26. With the X-acto knife trim out the center section of the template. Use the marker to trace the template profile onto the A-pillar (Figure: 11).



27. Remove the template.
28. Apply painters tape to the perimeter of the rectangle traced onto the A-pillar.
29. Grab the Dremel and cut out the center section of the A-pillar (Figure: 12).



Figure: 12

30. Grab the file and clean up the edges of the rectangle.
31. Remove the tape.
32. Locate the Daystar Switch Pod and the 4 push pins, and install the switch pod onto the A-pillar.
33. Install the switches into the Daystar Switch Pod (Figure: 13).
34. Attach accessory wiring to their respective switches.
35. Reinstall the A-pillar. The process is the reverse of the removal.
36. Congratulations on the installation of your Daystar A-pillar Switch Pod.



Figure: 13





Daystar® Lifetime GoEverywhere Limited Warranty

Your Daystar® Comfort Ride™ or Budget Boost™ leveling kit is covered by the following **Go Everywhere Lifetime Limited Warranty** provided exclusively by Daystar Products International, Inc., 841 South 71st Ave., Phoenix, AZ 85043 (“Daystar”).

What is Covered? Real Life Use, Off Road & On: Subject to the terms, exclusions and limitations herein, Daystar® warrants to the initial retail purchaser that your Comfort Ride™ or Budget Boost™ leveling kit shall be free of defects in material and workmanship for so long as it is properly installed on a single vehicle owned by the initial Daystar® purchaser.

What is Not Covered? Your Vehicle & Parts That Are Not Daystar’s GoEverywhere: Your Daystar **Limited Warranty** does not cover: (a) damage to your vehicle, vehicle systems (ex. electronic stability control), other products, components or property not manufactured by Daystar to our exclusive *GoEverywhere* standards, (b) customer choice of vehicle configuration/tire and wheel combinations contrary to Daystar® recommendations, warnings or applicable laws, (c) Acts of God, weather, corrosion, accidents, theft, vandalism, negligent misuse or intentional damage, other exclusions under your OEM Limited Warranty.

Remedy Limited to Repair/Replacement. Get back on your favorite trail fast. The exclusive remedy provided hereunder shall, upon Daystar’s inspection and option, be either repair or replacement of the Comfort Ride™ or Budget Boost™ leveling kit or parts covered under this **Limited Warranty**. Call us, and we will get you back wheelin’ (623-907-0081). All labor, removal, shipping and installation costs are the customer’s responsibility.

Other Exclusions –Limitation of Damages - Your Rights Under State Law. (Stuff Lawyers Say): At Daystar®, we aren’t big fans of lawyers, even ours. Still, he says our **Limited Warranty** has to include this stuff. In consideration of the purchase price paid, neither Daystar® nor any independent Daystar® distributor or repair person are responsible for any time loss, loss of vehicle use, rental costs, transportation, labor or for any incidental, consequential, punitive or other damages you may have or incur in connection with any part or product purchased. No Daystar® employee or independent distributor is authorized to make any statement or representation altering the terms of Daystar’s *GoEverywhere Lifetime Limited Warranty*. **Your exclusive remedy hereunder for covered parts is repair/replacement as described above.** This **Limited Warranty** gives you specific rights. You may also have other rights that vary from state to state. For example, some states do not allow limitations of how long an implied warranty lasts and/ or do not allow the exclusion or limitation of incidental or consequential damages, so the limitations and exclusions herein may not apply to you.

All other warranties are hereby disclaimed, except to the extent prohibited by applicable law in which case any implied warranty of merchantability, fitness for a particular purpose or other implied warranty are limited to a period of four (4) years from date of initial retail purchase. Daystar® reserves the rights to: (a) require invoice or other proof of purchase; (b) make future revisions to these products and **Limited Warranty** without prior notice or obligation to upgrade your Daystar® product.

© Daystar Products International, Inc., 9.15.13. All rights reserved.

DAYSTAR®

Truck and Jeep Accessories

ESTABLISHED IN 1977



LIKE US

SHARE US

WATCH US

FOLLOW US



Instagram

