



HEAD OFFICE/MANUFACTURING
33541 MacLure Road,
Abbotsford, BC, Canada V2S 7W2

US MAILING ADDRESS
1124 Fir Ave. PMB#403,
Blaine WA 98230 USA

Please fax this completed form to 1-604-853-6089 or email tech@bddiesel.com

BD Invoice # (if known):			
Customer Information			
Company:		Contact :	
Address:		Zip/Postal Code:	
Phone #		Fax #:	
Email:			
Vehicle Information			
Vin #:			
Mileage at installation:			
Transmission Serial Number :			
Installer Information			
Company:		Contact:	
Name:		Date of Install:	
Verification of pressures *(USE EITHER BD CONTROLLER OR TCM TUNING NOT BOTH)*			
Using BD Pressure Controller	Yes <input type="checkbox"/>	Using TCM Tuning	Yes <input type="checkbox"/>
Pressure at Idle (In Drive):			(Should be 60-120 PSI)
Pressure at wide open throttle (In Drive):			(Should be 230-260 PSI with a mechanical gauge)
** Wide open throttle pressures MUST be taken while the transmission is in lock up AFTER DRIVE LEARN has been completed. (300 PSI Manual Gauge)**			
68RFE Clutch Fluid Index Data Sheet			
Readings Must be done with a 300 PSI Gauge with the supplied adapter.			
	INITIAL	AFTER QUICK LEARN	DRIVE LEARN AFTER VALUE'S STABILIZE (50 MILES)
LR			
2-4 OR 2C			
UD			
OD			
4C			
Norm N-1 UD			
Alternate 4C			
1 st 2-3 OD			
Alternate 2C			
1 st N-1 UD			
	INITIAL	AFTER QUICK LEARN	DRIVE LEARN AFTER VALUE'S STABILIZE (50-100 KMS)
2-4 Shift			
2C			
1st N-UD			
1st 3-4 OD			
LR			
Alt 2C			
4C			
UD			
Norm N-D UD			
OD			
Please fill out applicable section as information differs dependent on model year.			