

## PREMIUM HIGH-EFFICIENCY ENGINE OIL FILTER (AC DELCO PF26, MOTORCRAFT FL-820S & MO-899)

**114000740**

### SPECIFICATIONS & PARAMETERS:

|                                         |                            |
|-----------------------------------------|----------------------------|
| Outer Diameter                          | 3.7 (95mm)                 |
| Thread Size                             | M22x1.5                    |
| Total Height                            | 5.9 inch (150mm)           |
| Gasket O.D.                             | 2.81 inch (71.5mm)         |
| Gasket I.D.                             | 2.44 inch (62mm)           |
| Filter Media Type                       | Synthetic                  |
| Media Surface Area                      | 330 in <sup>2</sup>        |
| Number of Pleats                        | 55 pleats                  |
| 50% Efficiency Rating*                  | 5 micron                   |
| 98% Efficiency Rating*                  | 10 micron                  |
| Anti-Drainback Valve                    | Silicone                   |
| Anti-Drainback Valve Temperature Rating | 275° F                     |
| Bypass Valve                            | Coil Spring w/ rubber seal |
| Bypass Diameter                         | 0.53 inch (13.4mm)         |
| Bypass Valve Pressure Rating            | 32 psi                     |
| Built-in Magnet                         | Yes                        |
| Wrenching Profile                       | 93mm 15-flute              |
| PPE Filter Wrench SKU                   | 114000759                  |

\*In accordance to ISO 4548-12 – methods of test for full-flow lubricating oil filters for internal combustion engines