FASS Diesel Fuel Systems

TITANIUM SIGNATURE SERIES

INSTALLATION MANUAL

ALL 1/2" FUEL PORTS



Ford POWER STROKE DIESEL

APPLICATION:

TS-F17-180F-140G
(140GPH@60-65PSI)

Powerstroke 6.7L
Bypassing the Factory Lift Pump
Standard Pickup Truck

2011-2016

DESIGNED, MACHINED & ASSEMBLED * IN THE USA *

LIFETIME WARRANTY AVAILABLE

Note: Cab and Chassis may require modifications

FASS DIESEL FUEL SYSTEMS® / ENGINEERED EXCELLENCE

Thank you for choosing FASS, from Diesel Performance Products, Inc.

FASS specializes in building extremely high-quality fuel products. We have earned an unsurpassed reputation for excellence in our industry by using only the highest-quality American-made components. In order to support our American workers and our American economy, more than 98+ percent of our products are manufactured completely in the United States.

Of course, that dedication to excellence comes at a price, but it is important to remember that price does not dictate quality-quality dictates price! We will never compromise by using cheaper, foreign-made components, like so many of our competitors do.

Customer satisfaction is our top priority and we strive always to provide outstanding customer service. Our Research and Development department, in conjunction with our Dealer Support Department, continually searches for ways to improve quality, expand our product line, and provide superb support. Our exclusive ViP Network ensures that customers receive the proper products and support at the local level. The extended lifetime warranty is only available on products purchased from the network. There is no warranty on products not purchased outside the network.

IMPORTANT:

In order to qualify for the lifetime extended warranty, your product registration form and proof of purchase from an authorized dealer must be submitted to FASS Fuel Systems within 30 days of purchase. Failure to comply will void the warranty. We have the right to deny any warranty believed to be false, altered or purchased through an unauthorized or terminated dealer. A current list of authorized dealers can be found on our website, FASSRide.com.

The complete conditions of the Limitation of Warranty can be found in the back of this manual, and FASSRide.com.

**For more information,
contact Technical Support:
Diesel Performance Products, Inc.
16234 State Hwy O.
Marthasville, MO 63357
636-433-5410**

www.fassride.com
(866) 769.3747



WARNING!

This product has NO WARRANTY unless:

1. It has been purchased from an Authorized or ViP FASS Dealer. If in doubt, check www.FASSRide.com.

2. It is registered within thirty (30) days of purchase.

Other conditions may apply. Please see full warranty information.

NOTE: **Warranty is void if product was purchased below FASS website advertised pricing.**

ATTENTION!

Before you begin installation

Register for your Warranty ONLINE at

https://www.fassride.com/register-a-warranty/

No online access, call our TECH Support at

1-866-769-3747

www.fassride.com
(866) 769.3747

FOLLOW THESE STEPS TO ENSURE A SIMPLE, CORRECT INSTALLATION OF YOUR NEW TITANIUM FUEL SYSTEM

ATTENTION:
Be sure to identify the proper FASS System and fuel line configuration. For help, our product finder can be found at www.FASSride.com. Follow the instructions to see fuel line detail.

1. *Pay close attention to ALL WARNINGS*

2. *Read all instructions before starting installation of this product.*

3. *Inventory the package components. Notify the place of purchase immediately of any parts missing or damaged.*

4. *The installation recommendations contained within are guidelines. Use good judgment and take into consideration your vehicle's accessories.*

5. *For best results in accuracy and efficiency (due to training, communication, and our relationship with our dealer network), we recommend a VIP FASS dealer for the installation. They are prepared to install the FASS fuel pumps with the most efficiency. If a situation or problem arises during the installation, the dealer is prepared to handle it. Diesel Performance Products, Inc. is not responsible for any installation mistakes.*

6. *If you have any questions or concerns that cannot be addressed with your dealer, email or call FASS.*

If any installation procedure is uncertain, contact FASS technical support.
Call customer service at 636-433-5410,
or send us an e-mail: techsupport@FASSride.com
with the following information:

Your name, address and daytime phone number
Model (TS-F17-180F-140G)
Last 6 digits of vehicles' VIN

Date of purchase
Nature of Your Concern
Serial number .....



www.fassride.com
(866) 769.3747

INSTALLATION MANUAL
TS-F17-180F-140G


(Installation Videos are available at www.fassride.com)

RECOMMENDED APPLICATION

TS-F17-180F-140G: Powerstroke (6.7L) 2011-2016 with stock - 700 horsepower

NOTE: Because of the higher fuel flow these systems have to offer, you may encounter problems with the stock fuel module. FASS can solve this issue with a Suction Tube Kit.

1. **Read all instructions before starting installation of this product!**
2. **Installing the improper FASS Pump can cause severe engine damage.**
3. **Secure vehicle from ROLLING!**
4. **Cab and Chassis may require modifications**
5. **Consult vehicle's manufacturers' instructions concerning the electrical system before attempting any electrical connections.**
6. **Flush and clean all brass fittings and fuel line from debris.**
7. **Keep debris from entering the internals of the system during installation. Getting debris in the water separator nipple can lock up the motor. If the motor does lock up from debris call FASS for technical assistance.**



9. **Wear safety glasses when operating power tools such as drills and grinders or when using a punch or chisel.**


10. **Properly secure lines to prevent chaffing.**

www.fassride.com
(866) 769.3747



WARNING!

Always be sure to fill the fuel tank to full after a new FASS installation. Failure to do so can result in excessive sound output, or priming issues!



www.fassride.com
(866) 769.3747

TITANIUM SIGNATURE SERIES 140 GPH


60-65PSI (Approximately)

Note: Going over 100 PSI WILL void warranty.

Rear View



Front View



PUMP GUIDE:

1. "E" To Engine
2. "R" Return to Tank
3. Serial Number
4. "T" Fuel Inlet
5. Electric Heater Ports
6. "G" Gauge Port

INSTALLATION GUIDE:

Step 1. Install Electrical Harness
Step 2. Prep the FASS
Step 3. Mount the FASS
Step 4. Fuel Line Supply
Step 5. Review Installation

www.fassride.com
(866) 769.3747


TITANIUM SIGNATURE SERIES 140 GPH

60-65 PSI (Approximately)

Note: Going over 100 PSI WILL void warranty.

NOTE: WARRANTY MAY BE VOID IF SILICONE BAND IS REMOVED FROM MOTOR!!


The silicone band is in place to retain motor wires, preventing damage to the electric motor.



CONTENTS

NOTE: ***Owner's Manual available for download on our website,***
www.FASSride.com






RELAY COVER



MP-9073



FL-1058x3"



FL-1002x9'



WH-1006-3



PFB-2002



PBR-2001



PFB-2001C

www.fassride.com
(866) 769.3747

MOUNTING PACKAGE CONTENTS



BHF-1005



TWO (2) PL-1005



ADD-A-CIRCUIT 46044



A624C56-55-05



DB-4646



PLB-1212



46251



TWO (2) RING TERMINAL



10-302



10-300



TWO (2) PL-1058



OR-212



BHN-1005



10-307



1/2" WASHERS



HEX BOLT 1/2" -20x1 3/4"



RVC-12

TWO (2) RVC-38



FOUR(4) HEX BOLT 3/8" -16x11/2"



THREE(3) HEX BOLT 1/4"-20x 13/4"



FOUR(4) LOCKING NUT 3/8"



THREE(3) WA-1001D




FOUR(4) 3/8" WASHERS




TWO (2) HC-1001

www.fassride.com
(866) 769.3747

MOUNTING PACKAGE CONTENTS



RS-2002




RS-2001



RS-2001C



ST-1005P



CABLE TIES



FL-1006



DIELECTRIC GREASE



TWO (2)
OR-017



OR-030


NOTE: THESE SPARE BASE O-RINGS ARE INCLUDED WITH THE KIT IN THE EVENT OF A PINCHED O-RING DURING ASSEMBLY

STEP 1:
INSTALL ELECTRICAL HARNESS

The installation of the electrical harness is done first, allowing power to be applied to the pump for lubrication purposes later in the installation.

NOTE: USE SUPPLIED DIELECTRIC GREASE SPARINGLY ON ALL ELECTRICAL CONNECTIONS! BE SURE TO GREASE RELAY PIGTAIL!









STEP 1:
INSTALL ELECTRICAL HARNESS

The installation of the electrical harness is done first, allowing power to be applied to the pump for lubrication purposes later in the installation.

Install the Relay Cover onto the relay on the FASS harness.






STEP 1:
INSTALL ELECTRICAL HARNESS

The installation of the electrical harness is done first, allowing power to be applied to the pump for lubrication purposes later in the installation.

NOTE: BE SURE TO INSTALL THE SUPPLIED 30 AMP FUSE INTO THE FASS WIRING HARNESS!!






STEP 1:
INSTALL ELECTRICAL HARNESS

The installation of the electrical harness is done first, allowing power to be applied to the pump for lubrication purposes later in the installation.


A. Using wire stripping tool remove excess insulation off the ADD-A-CIRCUIT 46044 and the single RED wire of WH-1006-3.



B. Place wire from ADD-A-CIRCUIT 46044 and WH-1006-3 into butt connector. Using crimping tool connect ADD-A-CIRCUIT 46044 and WH-1006-3 with butt connector. Install 46251 to ADD-A-CIRCUIT 46044 TOP slot. (Near the added circuit/wire). Route ADD-A-CIRCUIT 46044 lead through the fire wall using existing







C. Crimp the ring terminals to the red and green wires of the WH-1006-3 Wire Harness. Attach red wire to the positive terminal of the battery and the green wire to the negative terminal. Use supplied dielectric grease on all electrical connections.





STEP 1:
INSTALL ELECTRICAL HARNESS

D. Secure relay and fuse in an upright position, as shown, to prevent moisture from entering. Apply the supplied dielectric grease to all electrical connections to prevent moisture intrusion.



E. Route the extension to the engine bay fuse panel. Remove a fuse (maximum of 10A) that is "hot" when the key is on. Example: #54 or #55. Use a test probe to locate the "hot side" of the circuit in the fuse block. Install the fuse tap into the open location. Install the pulled fuse into the open space on the fuse tap. Disconnect the vehicles' battery and continue installation.





F. Route WH-1006-3 wire harness along frame rail to mounting location of pump. Completion of this step will be addressed in the mounting step.

STEP 2:
PREPARE SUCTION & RETURN LINES

Some of the photos are of a different application, procedures are the same.

NOTE: Before installing fittings make sure to inspect for burs or flare imperfections. When cutting fuel line make sure to blow out line to keep debris from moving forward.

Helpful Hint: Directions for removing factory lines.

1. Pull up on the locking tab (either blue or yellow),
2. Push in slightly on the connector,
3. Press down on the release tab,
4. Pull the connector straight off.



A. Before tank is removed or moved, identify ALL areas of clearance between the tank and the truck's bed for the best location to install the BHF assembly. With proper clearance, you want to install it as close to the Fuel sending unit as possible.



B. Remove the filler neck and overflow tubes from the truck by loosening the clamps at both ends.



STEP 2:
PREPARE SUCTION & RETURN LINES

C. Disconnect factory suction and return lines (refer to diagram at the beginning of step 2).



D. With the fuel tank empty of fuel, unbolt the tank straps and remove it from the vehicle.



E. Clean the fuel module area then remove the lock ring on the top of the fuel tank. **This is spring loaded, so, holding it down while removing the ring will prevent the sending unit from popping up and possibly causing damage.**




F. Note the location of the tab and arrow. Re-install the sending unit in the same location to prevent the fuel level arm from binding. Remove fuel tank module from fuel tank, be careful not to damage fuel level float.






STEP 2:
PREPARE SUCTION & RETURN LINES

G. Mark the location to mount the BHF-1005 on the fuel tank module, be sure fitting is clear of obstructions that will prevent improper installation. Using a 7/8" hole saw, drill at the marked location. Be sure to de-bur the drill hole to remove any excess plastic.


H. Install BHF-1005 into the hole drilled in previous step, install o-ring onto fitting along with BHN-1005. Be sure to apply red loctite or equivalent onto threads of BHF-1005 as this will ensure a leak free seal. Use channellock pliers to tighten nut to approximately 10 ft/lbs, be careful not to over-torque nut as this can damage fuel tank module. Check for proper gasket OR-212 compression.

I. Using a utility knife, remove factory convoluted tubing from the factory suction line as this will now be used for the FASS return. Be sure not to damage barbed fitting beneath convoluted tubing. Install FL-1006 onto the barbed fitting and route to the bottom of the fuel tank module. Secure FL-1006 to surrounding tubing. *IT MAY BE NECESSARY TO TRIM FL-1006 TO APPROPRIATE LENGTH!*






STEP 2:
PREPARE SUCTION & RETURN LINES

J. *VERY IMPORTANT:* Support fuel tank on both ends allowing the natural formation of the tank to take place. Failure to perform this step will hinder precision installation.



FUEL TANK SUPPORTS

K. Using a tape measure, measure from the bottom of the fuel tank to the top of the o-ring sealing surface where the fuel tank module makes contact and take note of the measurement. Compress fuel tank module to the exact height measurement taken in previous step, measure and mark ST-1005P with 1/2" clearance from bottom of fuel tank module. Cut ST-1005P to length and install onto BHF-1004 with hose clamp HC-1001. *NOTE: ACTUAL MEASUREMENTS WILL VARY FROM IMAGES!*
















STEP 2:
PREPARE SUCTION & RETURN LINES

L. Carefully reinstall fuel tank module into fuel tank, reinstall locking ring. Install 10-307 onto BHF-1005, fitting must be oriented facing FASS mounting location and free from obstruction. While tightening fitting nut, hold opposing end with a wrench to prevent damage to fuel module. Install PL-1058 onto 10-307 and torque with the same method used in previous step. Lubricate PL-1058 and push FL-1058 onto barb portion of fitting. Reinstall fuel tank into vehicle, reconnect electrical connector and factory fuel return line. Leave factory suction line disconnected as this is now the location for the FASS return, reconnect fill and vent tubes. Install A624C56-55-05 into 1 end of FL-1002 and connect to factory suction line on fuel tank module, opposing end of hose will later connect to FASS return.









NOTE:

ATTENTION: While installing fittings into Titanium pump DO NOT Apply side pressure to draw tube of pump






STEP 3:
MOUNT FUEL SYSTEM

NOTE: Before installing fittings make sure to inspect for burs or flare imperfections. When cutting fuel line make sure to blow out line to keep debris from moving forward.


A. Install 10-300 into the "E" port and 10-302 into the "T" port of the FASS, torque to 20 ft./lbs.
FITTINGS COME EQUIPPED WITH THREAD SEALANT, DO NOT USE THREAD TAPE







B. For fitting purposes, secure PBR-2001 to pump assembly lightly with (3) 1/4"-20x1 3/4 bolts and (3) WA-1001D. Assembly will be used in future steps for correct fitting of brackets. (Note: Bracket may be flipped to accommodate your application.)





STEP 3:
MOUNT FUEL SYSTEM

C. Assemble PFB-2001C and RS-2001C. RS will make contact with bed channel when assembled correctly. Insert the PFB-2002C assembly in to bed channel align the nut with the opening on the channel.








D. Secure PFB-2002 and RS-2001 with (1) hex bolt 1/2" -20 x 1 -3/4" and (1) 1/2" washer to PFB-2001C





E. Disconnect the factory power plug to the factory lift pump. Plug female plug of the WH-1006-3 harness into the FASS pump. Reconnect the vehicles battery. Turn key on. With pump operating, liberally spray WD-40 (or equivalent) into Water Separator nipple. This process helps lubricate the gear for easier initial priming.






STEP 3:
MOUNT FUEL SYSTEM

F. Position the PBR-2001 to the PFB-2002 pump assembly at the mounting location and check for fit. Once location is established, mark location for mounting in next step.




G. Assemble the FASS pump bracket PBR-2001 using the RS-2002 spacer between PFB-2002 and PBR-2001 bracket with 4-3/8 bolts, nuts, and washers. **Note: Torque bolts not flange nut.**





H. Once secure use 3-1 3/4 bolts and 3-WA-1001D spacers to mount the pump to the bracket.




STEP 3:
MOUNT FUEL SYSTEM

I. Apply motor oil to gasket located on filters. Attach to system and hand tighten.





Extreme Water Separator - Install XWS-3002 on side of pump with draw tube in the middle of the filter nipple.

Particulate Filter -Install PF-3001 on filter nipple without the draw tube. Make sure to insert O-Ring provided on nipple.





Note: O-Ring must be put back on suction side of pump. Failure to do so can result in priming issues, cavitation or pressure losses.

STEP 4:
INSTALL FUEL LINE

Caution: DO NOT use sealant on AN fittings

A. Route suction line from the BHF-1005 assy. to port 'T' on the FASS system. Cut FL-1058 to needed length. Insert PL-1058 using oil. Connect to 10-302 in port 'T'. Torque to 18 ft./lbs.



B. Route fuel line from the A624C56-55-05 to the 'R' port on the FASS system with a gentle bend. Cut and insert PL-1005 using oil. Attach fitting to the 'R' port. Do not use any sealant. Torque to 18 ft./lbs.



C. Insert PL-1005 into remaining fuel line using oil. Attach fuel line to the 'E' port of the FASS system. Torque to 18 ft./lbs. Route this line to the engine side of the factory lift pump. Do not cut at this time.



D. Bypass factory fuel pump.

E. Disconnect factory power to the lift pump. Drain fuel from factory lift pump.



STEP 4:
INSTALL FUEL LINE

F. Disconnect the yellow-clipped factory feed at the factory lift pump (refer to diagram at the beginning of step 2).




G. Measure fuel line from the FASS to the factory feed fitting. Cut and insert a PLB-1212 using oil. Oil the PLB and slide into the yellow





H. Disconnect both factory return lines from the factory lift pump (refer to diagram at the beginning of step 2). Insert DB-4646 into each return line fitting until you hear a click and tabs lock.



I. Clean and cap off the factory return ports with the two RVC-38 caps. Clean and cap off the factory feed port with the RVC-12 cap. Seal factory electrical connection with di-electric grease or similar to prevent corrosion.

Note: Secure all fuel lines with cable ties. Cable ties are an economical way to prevent the possibility of problems occurring!The factory suction line can be capped off or removed from the truck. The openings on the filter and tank will need to be capped off to keep debris from getting into lines or canister.

STEP 5:
REVIEW INSTALLATION

To assist with priming your FASS pump crack the XWS-3002 Put power to the FASS pump to activate the pump. When the tone of the pump changes you can tighten up the fuel filter. If you need a video of the priming process go to www.FASSride.com.



Note: The Red Plastic Plugs located in the "H" ports can stay in place fuel will not flow through these ports. Coolant can be plumbed into these ports to heat the fuel in the Winter months.

www.fassride.com
(866) 769.3747




Fuel System Must Be Flushed!

To ensure no foreign debris has entered the fuel system, you must remove the engine feed line at the engine connection, power the FASS on and allow fuel to flush all fuel lines into a bucket.

FAILURE TO PERFORM THIS FLUSH CAN RESULT IN DAMAGED FUEL INJECTION SYSTEM COMPONENTS!

STEP 5:
REVIEW INSTALLATION



Note: O-Ring must be put back on suction side of pump. Failure to do so can result in priming issues, cavitation, or pressure loses.

1. Blow out any open lines/cover any open ports
2. Bolts and fasteners properly tightened?
3. Electrical harness and fuel lines secured and properly tightened? Reconnect the battery.
4. Has the system been primed?
    a. Turn key to the ignition position, turning on the FASS pump for 15 sec..
    b. Crank engine and allow to run for at least 1 minute.
5. Check for leaks.
6. Start the engine
7. Recheck all fluid and filter connections for leaks
8. This pump comes with a 1 Year Manufacturer's Warranty based on the date it has been manufactured. To receive your extended Lifetime Warranty, you have 30 days from date of purchase to send the completed warranty information

www.fassride.com
(866) 769.3747

LIMITATION OF LIFETIME WARRANTY

Disclaimer: To help insure you receive the proper system and customer support at the local level, FASS has a VIP and Authorized Dealer network representing FASS products. This is one reason you must purchase through a dealer to comply with our warranty policies. If you do not, there is no warranty! We recommend you go to www.FASSride.com, click "Find a Dealer", put in their ZIP code, select the type of dealer, and see if the company you purchased from is listed. If they are not, put their phone number in the field below the ZIP code field to see if they are listed. Below these two fields is a list of "Terminated/Unauthorized" dealers. You may want to review this list. If the company is not listed or is on the "Terminated/Unauthorized" list, we suggest you return the product immediately to that dealer and call FASS. We'll recom-mend you to the nearest dealer.

Diesel Performance Products, Inc. (hereafter "SELLER") gives Limited Warranty as to description, quality, merchantabil-ity, fitness for any product's purpose, productiveness, or any other matter of SELLER'S product sold herewith. The SELL-ER shall be in no way responsible for the product's open use and service and the BUYER hereby waives all rights other than those expressly written herein. This Warranty shall not be extended or varied except by a written instrument signed by SELLER and BUYER.

When MANUFACTURER receives the "ORIGINAL" PRODUCT REGISTRATION form with a copy of the "BILL OF SALE/SALES RECEIPT" within 30 days of the sale, then the following applies! The Warranty will then and only then be validated to that of which typically accompanies your unit for your specific application from the date of sale or for recommended service life and limited solely to the original purchaser and/or vehicle and parts contained within the product's kit. This warranty does not cover normal wear on consumable items such as but not limited to filters, fuel line, wire harness & etc. The warranty does not cover seized gears due to lack of filtration. Warranty is voided if used with other than diesel fuel. Returned items will arrive prepaid to the place of purchase. Diesel Performance Products, Inc. will repair, without cost, any product found to be defective during the warranty period; parts only, or at its option, will replace such products in exchange for the product. Repair or replacements are warranted for the remainder of the original warranty peri-od. All Warranty claims are subject to approval by Diesel Performance Products, Inc.

A Return Material Authorization (RMA) number must be obtained before any product is to be returned to Diesel Performance Products, Inc. for warranty consideration, repair or product return. Requests for product returns must be offset by an equal value order. Return parts must be completed and in resalable condition. No returns after 30 days.

The following information is required to obtain a RMA number before returning product:

Your Name, Address, and Phone Number's
Model and Serial Number (Not Motor Number) Example: Model HD Series, Serial: 00125966 VIN Number of Vehicle
Date of Purchase
Nature of Problem

RMA and Product Serial Number must be on all paperwork and correspondence. Failure to obtain the required information or paperwork will result in $25.00/item penalty and delay or denial of any warranty claim.
Under no circumstances shall the SELLER and/or MANUFACTURER be liable for any labor charged or travel time in-curred in diagnosis for defects, removal, or reinstallation of this product, or any other contingent expenses.
Under no circumstances shall the SELLER and/or MANUFACTURER be liable for any damage or expenses insured by reason of the use or sale of any such equipment. This warranty does not apply to products which Diesel Performance Prod-ucts, Inc. has determined to have been misused or abused, improperly maintained by the user, or where the malfunction or defect can be attributed to the use of non-genuine Diesel Performance Products, Inc. parts.

IN THE EVENT THAT THE BUYER DOES NOT AGREE WITH THIS AGREEMENT: THE BUYER MAY PROMPLY RETURN THIS PRODUCT, IN A NEW AND UNUSED CONDITION, WITH A DATED PROOF OF PURCHASE, TO THE PLACE OF PURCHASE WITHIN THIRTY (30) DAYS FROM DATE OF PURCHASE FOR A FULL REFUND LESS SHIPPING.

THE INSTALLATION OF THIS PRODUCT INDICATES THAT THE BUYER HAS READ AND UNDERSTANDS THIS AGREEMENT AND ACCEPTS ITS TERMS AND CONDITIONS.

®FASS Diesel Fuel Systems is a Registered Trademark of Diesel Performance Products, Inc. © Copyright 2016, Diesel Performance Products, Inc.

NOTES: